IM C5501CE

MAIN SPECIFICATIONS

GENERAL

Warm-up time	21 seconds
First copy speed: BW	2.9 seconds
First copy speed: full colour	4.2 seconds
Recovery time	1.2 seconds
Continuous output speed	55 ppm
Memory: standard	4 GB
Memory: maximum	6 GB
HDD: standard	320 GB
ARDF capacity	100 sheets
SPDF capacity	220 sheets
Weight ARDF model	99 kg
Weight SPDF model	104 kg
Weight PLATEN model	89.5 kg
Dimensions ARDF model: WxDxH	587 x 701 x 913 mm
Dimensions SPDF model: WxDxH	587 x 701 x 963 mm
Dimensions PLATEN model: WxDxH	587 x 701 x 852 mm
Power source	220 - 240 V, 50 - 60 Hz

COPIER

Multiple copying	Up to 999 copies
Resolution	600 dpi
Zoom	From 25% to 400% in 1% steps

PRINTER

First print speed: B/W	2.5 seconds
First print speed: full colour	3.9 seconds
CPU	ApolloLake E3930 1.3 GHz
Printer language: standard	PCL5c, PCL6, PostScript 3 (emulation), PDF direct (emulation)
Printer language: option	Genuine Adobe® PostScript®3™
Print resolution: maximum	1,200 x 1,200 dpi
Network interface: standard	Ethernet 10 base-T/100 base-TX/1000 base-T USB Host I/F Type A USB Device I/F Type B Bluetooth
Network interface: option	Wireless LAN (IEEE 802.11a/b/g/n)
Mobile printing capability	Apple AirPrint, Mopria®, Ricoh Smart Device Connector
Network protocol	TCP/IP (IP v4, IP v6)
Windows® environments	Windows® 10, Windows® 11, Windows® Server 2012R2, Windows® Server 2016, Windows® Server 2019, Windows® Server 2022
Mac OS environments	Macintosh OS X v10.15 or later
UNIX environments	UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux Enterprise
Other supported environments	IBM iSeries

SCANNER

Scanning speed: ARDF (A4 LEF, B&W full colour)	80 ipm (200-300 dpi)
Scanning speed: SPDF (A4 LEF, 200dpi, B&W full colour)	120 ipm (simplex) - 240 ipm (duplex)
Resolution: maximum	1,200 dpi
Compression method	BW: TIFF (MH, MR, MMR, JBIG2), Grayscale - Colour: JPEG Colour: JPEG
File formats	Single Page TIFF, Single page JPEG, Single page High compression PDF, Single page PDF/A, Multi page TIFF, Multi page PDF, Multi page High compression PDF, Multi page PDF/A
Scan modes	E-mail, Folder, USB

FAX

Circuit	PSTN, PBX
Transmission speed	2 seconds
Modem speed: maximum	33.6 Kbps
Resolution: standard	8x3.85 line/mm, 200x100 dpi
Compression method	MH, MR, MMR, JBIG
Scanning speed : ARDF (A4 LEF)	68 spm
Scanning speed : SPDF (A4 LEF)	81 spm
Memory: standard	4 MB (320 pages)

IM C5501CE

MAIN SPECIFICATIONS

PAPER HANDLING

Recommended paper size	Standard paper tray(s) : SRA3, A3, A4, A5, A6, B4, B5, B6, Envelopes Optional paper tray(s) : SRA3, A3, A4, A5, A6, B4, B5, B6, Envelopes Bypass tray : SRA3, A3, A4, A5, A6, B4, B5, B6, Envelopes, Custom Size paper (Width: 90 mm - 320 mm, Length: 148 mm - 1,260 mm)
Paper input: standard	1,200 sheets
Paper input: maximum	2,300 sheets
Paper output: standard	500 sheets
Paper output: max.	1,625 sheets
Paper weight	Trays: 60 - 300 g/m² Bypass: 52 - 300 g/m² Duplex: 60 - 300 g/m²
Paper types	Plain paper, Recycled paper, Special paper, Colour paper, Letterhead, Cardstock, Preprinted paper, Bond paper, Coated paper, Envelope, Gloss paper, Label paper, OHP

ECOLOGY

Power consumption: max.	< 1,450 W
Power consumption operation: B&W	791 W
Power consumption operation: Full colour	909 W
Power consumption: ready	40.7 W
Power consumption: sleep	0.86 W
TEC*	0.72 kWh/week

* It is a reference value based on the ENERGY STAR Ver.3.0 test method.

INPUT/OUTPUT TRAYS AND FINISHER OPTIONS

2x 550-sheet paper tray (SRA3, A3, A4, A5, A6, B3, B4, B5, B6, 60-300 g/m²), 1,000-sheet Hybrid finisher, 1,000-sheet Booklet finisher (A3, A4, B4, B5), 2,000-sheet Booklet finisher, 500-sheet Internal finisher

OTHER OPTIONS

Fax unit, Low cabinet, Punch units, PostScript 3, IEEE 802.11 a/b/g/n, OCR unit, Card reader cover, Bridge unit

CONSUMABLES

Starter toner	Black: 14,500 prints Colour: 5,500 prints
Toner (black)	32,500 prints
Toner (cyan/magenta/yellow)	24,000 prints
Waste toner bottle	100,000 sheets
Consumable yield based on 5% coverage/A4	

For availability of models, options and software, please consult your local supplier.

Ricoh Europe (Netherlands) B.V.
John M. Keynesplein 10-B
1066 EP Amsterdam
The Netherlands

+31 (0)20 5774111

ricoh-europe.com

RICOH
imagine. change.

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The images in this brochure are not real photographs and slight differences in detail might appear, including in relation to colour. Not all services and solutions are available to all customers. Copyright © 2025 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.